







DECLARACIÓN AMBIENTAL DE PRODUCTO ENVIRONMENTAL PRODUCT DECLARATION

DAPcons®.

According to ISO 14025 and EN UNE 15804 + A2:2020






Product		
Owner		
Product description		
i roddot doddriptioi	•	
PCR Reference		
Production plant		
Validity		
From:	To:	
I IUIII.	10.	

The validity of DAPcons® is subject to the conditions of DAPcons® regulations. The relevant version of this DAPcons® is included in the register kept by the CAATEEB; for more information, consult the Program Operator website: www.csostenible.net



ENVIRONMENTAL PRODUCT DECLARATION. EXECUTIVE SUMMARY









ENVIRONMENTAL PRODUCT DECLARATION

1. PRODUCT DESCRIPTION AND APPLICATION













2. LIFE CYCLE PHASES DESCRIPTION

Raw materials (A1 and A	2)		
Manufacturing (A3)			





2.2. Construction (A4 and A5)

Product transport to the building site (A4)

Table 1. Transport scenarios of product to the building site

Destination	Type of transport	Percentage (%)	Average Km
Spain			
Europe			
Rest of the world			
		Total 100%	

Construction and instalation process (A5)







2.3. Product use (B1-B7)

2.4. End-of-life (C1-C4)

2.5. Benefits and loads beyond the system boundary (D)





3. LIFE CYCLE ASSESSEMENT

3.1. Unit

3.2. System boundary

Table 2. Declared modules

Pro	duct st	age	Constr Proces Stage		Use stage End of life stage				Use stage End of life stage				e	Benefits and loads beyond the system boundaries		
Raw materials supply	Transport	Manufacturing	Transport	Installation process	Use	Maintenance	Repair	Replacement	Refurbishment	Operational Energy use	Operational water use	De-construction	Transport	Waste processing	Disposal	Reuse, recovery, recycling potential
A1	A2	A3	A4	A5	B1	B2	ВЗ	В4	B5	В6	B7	C1	C2	СЗ	C4	D

X = Included in LCA

MND = Module not Declared







3.3. Data analysis for the life cycle (LCA)

Table 3. Indicators of the environmental impact







Table 4. Use of resources, waste and material outflows parameters

EXCEL







Table 5. Kg of biogenic carbon

Product	Kg
Packaging	Kg

3.4. Recommendations of this DAP

3.5. Cut-off rules

3.6. Additional environmental information

3.7. Other data





4. TECHNICAL INFORMATION AND SCENARIOS

4.1. Transport from the factory to the building site (A4)

Parameter	Parameter expressed by functional unit
Type and fuel consumption, type of vehicle used for transportation	
Distance	
Capacity utilization (including empty return)	
Apparent density of transported product	
Useful capacity factor (1, <1, or> 1 for products that are packed compressed or nested)	

4.2. Installation processes (A5)

Parameter	Parameter expressed by functional unit
Construction ancillary materials (specifying each material)	
Water consumption	
Consumption of other resources	
Quantitive despription of the type of energy (mix regional) and consumption during the installation process	
Materials waste on site before waste treatment, generated by the installation of the product (specify by type)	
Material outputs (specified by type) as a result of waste treatment on the building site. For example: collection for recycling, energy valuation, disposal (specified by route)	
Emisions to the air, ground or water	





Reference service life (B1)

Parameter	Parameter expressed by functional unit
Reference service life (RSL)	
Properties and characteristics of the product	
Requirements (ways of using, maintenance frequency, repair, etc.)	

4.4. Maintenance (B2), repair (B3), replacement (B4) or refurbishement (B5)

B2 Maintenance				
Parameter	Parameter expressed by functional unit			
Maintenance, for example: cleaning agent, type of surfactant				
Maintenance cycle				
Auxiliar materials for the maintenance process (specifying each material)				
Net consumption of fresh water				
Loss of material during maintenance or repair (specifying the type)				





B3 Repair	
Parameter	Parameter expressed by functional unit
Repair process	
Inspection process	
Repair cycle	
Auxiliary materials (specifying each material), e.g. lubricant	
Energy input during repair, vector type energy (for example, electricity) and quantity	
Energy input during the process of renovation (amount and type of energy vector)	
Loss of material during repair (specifying each material)	
Net consumption of fresh water	

B4 Replacement				
Parameter	Parameter expressed by functional unit			
Energy input during replacement, for example for the use of cranes (quantity and energy vector)				
Worn out parts replacement in the life cycle of the product (specifying each material)				
Replacement cycle				





B5 Rehabilitation	
Parameter	Parameter expressed by functional unit
Rehabilitation process	
Rehabilitation cycle	
Energy input during rehabilitation, for example for the use of cranes (quantity and energy vector)	
Material input for rehabilitation, including auxiliary materials (specified by material)	
Material waste during rehabilitation (specifying each material)	
Other scenario development assumptions	

4.5. Useful life reference

Parameter	Parameter expressed by functional unit
Useful life reference	
Product declared properties, finishes, etc.	
Application design parameters (manufacturer's instructions)	
Workmanship quality estimation, when installed in accordance with the manufacturer's instructions	
Outdoor environment for outdoor applications. For example, weather, pollutants, UV radiation, temperature, etc.	





Indoor environment for indoor applications. For example, temperature, humidity, exposure to chemicals	
Terms of use. For example, frequency of use, mechanical exposure, etc.	
Maintenance. For example, the required frequency, etc.	

4.6. Operational use of energy (B6) and water (B7)

Parameter	Parameter expressed by functional unit
Construction ancillary materials (specified by material)	
Energy vector type. For example, electricity, natural gas, district heating	
Equipment output power	
Net fresh water consumption	
Characteristic features (energy efficiency, emissions, etc.)	
Other scenarios development assumptions. For example, transportation	





4.7. End of life (C1-C4)

Process	Parameter expressed by functional unit
Collection processes (specified by types)	
Recovery systems (specified by type)	
Elimination	
Assumptions for the development of scenarios. For example, transportation	

5. ADDITIONAL INFORMATION







6. PCR AND VERIFICATION

This declaration is based on the Document
Independent verification of the declaration and data according to ISO 14025 and UNE EN15804 + A2
Internal External
Independent verifier appointed
Verification date
References

Administrator of programme operator

Col·legi d'Aparelladors, Arquitectes Tècnics i Enginyers de l'Edificació de Barcelona (CAATEEB) Bon Pastor 5, 08021 Barcelona www.apabcn.cat



